

ELRO KETTLES 2300:

TECHNICAL SPECIFICATION

NON PRESSURE

PRESSURE

Type	tilting				non tilting						non tilting		
	JK1 - 75	JK1 - 100	JK2 - 140	JK3 - 200	JR1 - 60	JR1 - 80	JR1 - 100	JR2 - 140	JGN2	JGN3	DGN2	DGN3	
Dimensions / Capacity / Power													
Volume (lit.)	84	104	150	221	69	88	104	150	194	295	194	295	
Bassin dimensions Ø (mm)	Ø x Height	500 x 430	500 x 530	600 x 530	750 x 500	500 x 350	500 x 450	500 x 530	600 x 530				
	Width x Depth x Height									680 x 550 x 531	1030 x 550 x 531	680 x 550 x 531	1030 x 550 x 531
External dimensions (mm)	Width	1020	1020	1120	1270	780	780	780	880	1050	1400	1050	1400
	Depth	800	800	800	800	800	800	800	800	800	800	800	800
	Height	400	400	400	400	700	700	700	700	700	700	700	700
Electrical connected load (kW / A)		17.1 / 25.0	17.1 / 25.0	21.0 / 30.5	27.0 / 39.0	14.2 / 24.0	17.1 / 25.0	17.1 / 25.0	21.0 / 30.5	30.0 / 43.5	45.0 / 65.0	30.0 / 43.5	45.0 / 65.0
Voltage 400 V 3LPE 50/60 Hz		●	●	●	●	●	●	●	●	●	●	●	●
Installation													
ELRO Installation wall		○	○	○	○	○	○	○	○	○	○	○	○
ELRO Hygiene installations		○	○	○	○	○	○	○	○	○	○	○	○
ELRO CNS base		○	○	○	○	○	○	○	○	○	○	○	○
ELRO Feet		○	○	○	○	○	○	○	○	○	○	○	○
Wall mounting 400 mm		○	○	○	○	○	○	○	○				
Wall mounting 700 mm		○	○	○	○	●	●	●	●	○	○	○	○
Concrete base		○	○	○	○	○	○	○	○	○	○	○	○
Mobile version		■	■	■	■	■	■	■	■	■	■	■	■

● Standard ○ Optional