

ELRO MULIFUNCTIONAL PAN 2300:

TECHNICAL SPECIFICATION

PRESSURE PAN

Type	non tilting				tilting				
	DBGN22	DBGN23	DBGN32	DBGN33	DBKGN22	DBKGN23	DBKGN32	DBKGN33	
Dimensions / Capacity / Power									
Frying surface (mm)	Width	680	680	1030	1030	680	680	1030	1030
	Depth	550	550	550	550	550	550	550	550
Volume (lit.)	90	112	136	170	86	108	131	165	
Bassin dimensions Ø (mm)									
Crucible depth (mm)	240	300	240	300	240	300	240	300	
External dimensions (mm)	Width	1050	1050	1400	1400	1200	1200	1550	1550
	Depth	800	800	800	800	800	800	800	800
	Height	700	700	700	700	700	700	700	700
Electrical connected load (kW / A) with EDS	15.1 / 21.7	15.1 / 21.7	23.5 / 33.9	23.5 / 33.9	15.1 / 21.7	15.1 / 21.7	23.5 / 33.9	23.5 / 33.9	
Electrical connected load (kW / A) with EDP (increased)	22.0 / 31.8	22.0 / 31.8	33.0 / 47.8	33.0 / 47.8	22.0 / 31.8	22.0 / 31.8	33.0 / 47.8	33.0 / 47.8	
Electrical connected load with high-speed (kW / A)	30.1 / 43.7	30.1 / 43.7	43.5 / 62.8	43.5 / 62.8					
Voltage 400 V 3LPE 50/60 Hz	●	●	●	●	●	●	●	●	
Installation									
ELRO Installation wall	○	○	○	○	○	○	○	○	
ELRO Hygiene installations	○	○	○	○	○	○	○	○	
ELRO CNS base	○	○	○	○	○	○	○	○	
ELRO Feet	○	○	○	○	○	○	○	○	
Wall mounting 400 mm	○	○	○	○	○	○	○	○	
Wall mounting 700 mm	○	○	○	○	○	○	○	○	
Concrete base	○	○	○	○	○	○	○	○	
Mobile version	■	■	■	■	■	■	■	■	

● Standard ○ ■ Optional

ELRO MULIFUNCTIONAL PAN 2300:

TECHNICAL SPECIFICATION

NON PRESSURE PAN

Type	non tilting						tilting				
	PGN21	PGN22	PGN23	PGN31	PGN32	PGN33	PKGN22	PKGN23	PKGN32	PKGN33	
Dimensions / Capacity / Power											
Frying surface (mm)	Width	680	680	680	1030	1030	1030	680	680	1030	1030
	Depth	550	550	550	550	550	550	550	550	550	550
Volume (lit.)		54	90	112	82	136	170	86	108	131	165
Bassin dimensions Ø (mm)											
Crucible depth (mm)		145	240	300	145	240	300	240	300	240	300
External dimensions (mm)	Width	1050	1050	1050	1400	1400	1400	1200	1200	1550	1550
	Depth	800	800	800	800	800	800	800	800	800	800
	Height	700	700	700	700	700	700	700	700	700	700
Electrical connected load (kW / A) with EDS		15.1 / 21.7	15.1 / 21.7	15.1 / 21.7	23.5 / 33.9	23.5 / 33.9	23.5 / 33.9	15.1 / 21.7	15.1 / 21.7	23.5 / 33.9	23.5 / 33.9
Electrical connected load (kW / A) with EDP (increased)		22.0 / 31.8	22.0 / 31.8	22.0 / 31.8	33.0 / 47.8	33.0 / 47.8	33.0 / 47.8	22.0 / 31.8	22.0 / 31.8	33.0 / 47.8	33.0 / 47.8
Electrical connected load with high-speed (kW / A)											
Voltage 400 V 3LPE 50/60 Hz		●	●	●	●	●	●	●	●	●	●
Installation											
ELRO Installation wall		○	○	○	○	○	○	○	○	○	○
ELRO Hygiene installations		○	○	○	○	○	○	○	○	○	○
ELRO CNS base		○	○	○	○	○	○	○	○	○	○
ELRO Feet		○	○	○	○	○	○	○	○	○	○
Wall mounting 400 mm		○	○	○	○	○	○	○	○	○	○
Wall mounting 700 mm		○	○	○	○	○	○	○	○	○	○
Concrete base		○	○	○	○	○	○	○	○	○	○
Mobile version			■	■		■	■	■	■	■	■

● Standard ○ Optional