

# Cooking – Mixing – Cooling

## MixaTherm-Stirring Kettle

### VERSATILE – EFFICIENT – POWERFUL

- Multifunction: cooking, stirring, cooling, mashing or whipping until fluffy
- Temperatures at the base of the kettle up to 120 °C
- Stirring with up to 477 NM from 5-155 rpm
- 300 liters recooling from 90 °C to 3 °C in just 66 minutes
- Low noise emission of less than 55 DB

### YOUR ADVANTAGES

- Maximum production quantities with outstanding food quality and absolute hygiene
- Relief of blast chiller capacities
- HACCP-compliant recooling
- High energy efficiency and high cooling effect with low water consumption
- Easy cleaning thanks to special cleaning programme and cleaning tools



# Cooking – Mixing – Cooling

## MixaTherm-stirring Kettle



**MultiMix**



**OptiMix**



**MaxiMix**

MultiMix   OptiMix	40	60	80	100	120	150	200
Dimensions W x D x H in mm (with standard columns)	1246 x 1000 x 900	1295 x 1000 x 900	1375 x 1000 x 900	1375 x 1080 x 900	1335 x 1080 x 900	1492 x 1090 x 900	1542 x 1170 x 900
Electrical connected load in kW 440V 3N AC 50Hz	16.1	16.1	16.1	21.1	21.1	32.2	32.2
Connected load steam in kW 440V 3N AC 50Hz	1.2	1.2	1.2	1.2	1.2	2.3	2.3
Gross capacity in liters	48	70	91	113	133	169	222
Spout height in mm	400   600	400   600	400   600	400   600	400   600	400   600	400   600
QuickChill (re-cooling)	no   no	no   no	no   yes	no   yes	no   no	no   yes	no   yes

  

MultiMix   OptiMix	250	300		MaxiMix	400	500
Dimensions W x D x H in mm (with standard columns)	1640 x 1250 x 900	1740 x 1330 x 900		Dimensions W x D x H in mm (with standard columns)	1840 x 1450 x 900	1840 x 1450 x 1017
Electrical connected load in kW 440V 3N AC 50Hz	48	48		Electrical connected load in kW 440V 3N AC 50Hz	63.0	63.0
Connected load steam in kW 440V 3N AC 50Hz	3.1	3.1		Connected load steam in kW 440V 3N AC 50Hz	3.1	3.1
Gross capacity in liters	278	334		Gross capacity in liters	447	547
Spout height in mm	400   600	400   600		Spout height in mm	400	400
QuickChill (re-cooling)	no   yes	no   yes		QuickChill (re-cooling)	yes	yes

**CONTACT:**

**ELRO-WERKE AG**  
 Wohlerstrasse 47  
 CH-5620 Bremgarten  
[www.elro.ch](http://www.elro.ch)

**ELRO Switzerland and International**  
 Tel. +41 56 6489-111  
[verkauf@elro.ch](mailto:verkauf@elro.ch)